



Z1000 / 2010

Wild at heart

State-of-the-art styling and a clean sheet design philosophy have resulted in a bold new Z1000 taking the Streetfighter category to new heights.

£ 8,499

Price includes VAT at 17.5%, delivery to dealer and preparation of motorcycle. Government charges are charged in addition



Metallic Chestnut
Brown



Pearl Stardust White
/ Candy Burnt
Orange



Metallic Spark Black
/ Atomic Silver

Kawasaki

Features

Z1000 / 2010



All-new Engine



Aggressive Styling



All-new Aluminium Twin-tube Frame



New 5-spoke cast wheels



Cool Air System



Fully adjustable front fork

More features



Horizontal back-link



New adjustable instrument panel



Brakes



Quad-style muffler



LED Tail light



Fat-type handlebar



Seat cover

Accessories

Z1000 / 2010



AKRAPOVIC EXHAUST*
£ 982.95



CRANK CASE RINGS
£ 64.95



KNEE PADS
£ 24.95

More accessories



PILLION SEAT COVER
£ 209.95




TANK PAD INCL. KEY
FOB GUARD
£ 32.95



WINDSCREEN
£ 69.95



BIKE COVER INDOOR
£ 30.95



BIKE COVER OUTDOOR
£ 40.95

M10 BOBBIN SET
£ 17.95

Engine

Engine type	Liquid-cooled, 4-stroke In-Line Four
Displacement	1,043 cm ³
Bore x stroke	77.0 x 56.0 mm
Compression ratio	11.8:1
Valve/Induction system	DOHC, 16 valves
Fuel system	Fuel injection: ø38 mm x 4 (Keihin) with oval sub-throttles
Ignition	Digital
Starting	Electric
Lubrication	Forced lubrication, wet sump

Transmission

Transmission	6-speed, return
Final Drive	Sealed chain
Primary reduction ratio	1.627 (83/51)
Gear ratios: 1st	2.600 (39/15)
Gear ratios: 2nd	1.950 (39/20)
Gear ratios: 3rd	1.600 (24/15)
Gear ratios: 4th	1.389 (25/18)
Gear ratios: 5th	1.238 (26/21)
Gear ratios: 6th	1.136 (25/22)
Final reduction ratio	2.800 (42/15)
Clutch	Wet multi-disc, manual

Frame

Frame type	Aluminium twin-tube
Rake/Trail	24.5° / 103 mm
Wheel travel, front	120 mm
Wheel travel, rear	135 mm
Tyre, front	120/70ZR17M/C (58W)
Tyre, rear	190/50ZR17M/C (73W)
Steering angle, left / right	31° / 31°

Suspension

Suspension, front	41 mm inverted fork with stepless compression and rebound damping and spring preload adjustability
Suspension, rear	Horizontal Back-link, gas-charged, with stepless rebound damping and spring preload adjustability

Brakes

Brakes, front	Dual semi-floating 300 mm petal discs
Brakes, rear	Dual radial-mount, opposed 4-piston Single 250 mm petal disc Single-piston

Dimensions

Dimensions (L x W x H)	2,095 mm x 805 mm x 1,085 mm
Wheelbase	1,440 mm
Ground Clearance	140 mm
Seat height	815 mm
Fuel capacity	15 litres
Curb Mass	218 kg / 221 kg (ABS)

Performance

Maximum power	101.5 kW {138 PS} / 9,600 rpm
Maximum torque	110 Nm {11.2 kgf-m} / 7,800 rpm